

NetComm AG400 Thermal Ticket Printer

AG400 is a plug and play thermal ticket printer that connects to the NetComm HS1100 wireless hotspot gateway or IAC3000 internet access controller to print out ticket for on-demand user accounts. All billing profile configurations and settings are made in the HS1100 or IAC3000; no configurations are required to be made in the AG400. For detail explanation on how to configure billing profiles, please refer to the HS1100 or IAC3000 product user manual.

1. Package Contents

The standard package of the AG400 Thermal Ticket Printer includes:

- AG400 Ticket Printer with paper x 1
- Power cable kit x 1 (AC Input: 100~240V / DC Output: 9~12V, 3A power adaptor)
- Thermal paper roll x 1
- RJ11 Cable x 1

2. Product Overview

(Front Side)



(Back Side)



Please note:

DB25 and RJ11 connectors basically have the same function; they are used to connect to different model. The 'DB25 Connector' is not used in HS1100 or IAC3000 system. No connection is needed to this DB25 connector.

3. Installation





Remove the cover, then insert the paper roll and press “LF” to let the paper be drawn into the print mechanism. Then close the cover.



Connect the HS1100/AC3000 to the AG400 Thermal Ticket Printer via the RJ11 cable provided.



Click on Function Selection button to choose the billing rule.

AG400 Thermal Ticket Printer quick installation completed